

RCM Series - Salamanders

RCM-24



Temperature Range	BTUs (Natural Gas)	Dimensions - LxWxD mm / in
200°F - 400°F	20,000	580 / 22 3/4" 610 / 24" 475 / 18 3/4"

- Gas salamander Gas infrared burner for better and even heat distribution
- Extra large infrared burner to cover large cooking area
- Instant heating up, no need to pre-heat
- Standby pilot for easy start
- Three rack positions Chrome coating wiring grid
- Zinc alloy knob with chrome coating
- Oil collector at the bottom
- Easy conversion from natural gas to Propane or vice versa
- Stainless steel in the front and sides
- Manual control
- 3/4" NPT rear gas connection

RCM Series - Salamanders

RCM-36



Temperature Range	BTUs (Natural Gas)	Dimensions - LxWxD mm / in
200°F - 400°F	30,000	580 / 22 3/4" 914 / 36" 475 / 18 3/4"

- Gas salamander Gas infrared burner for better and even heat distribution
- Extra large infrared burner to cover large cooking area
- Instant heating up, no need to pre-heat
- Standby pilot for easy start
- Three rack positions Chrome coating wiring grid
- Zinc alloy knob with chrome coating
- Oil collector at the bottom
- Easy conversion from natural gas to Propane or vice versa
- Stainless steel in the front and sides
- Manual control
- 3/4" NPT rear gas connection

RCM Series - Salamanders

RCM-48



Temperature Range	BTUs (Natural Gas)	Dimensions - LxWxD mm / in
200°F - 400°F	40,000	580 / 22 3/4" 1219 / 48" 475 / 18 3/4"

- Gas salamander Gas infrared burner for better and even heat distribution
- Extra large infrared burner to cover large cooking area
- Instant heating up, no need to pre-heat
- Standby pilot for easy start
- Three rack positions Chrome coating wiring grid
- Zinc alloy knob with chrome coating
- Oil collector at the bottom
- Easy conversion from natural gas to Propane or vice versa
- Stainless steel in the front and sides
- Manual control
- 3/4" NPT rear gas connection

RCM Series - Salamanders

RCM-60



Temperature Range	BTUs (Natural Gas)	Dimensions - LxWxD mm / in
200°F - 400°F	50,000	580 / 22 3/4" 1524 / 60" 475 / 18 3/4"

- Gas salamander Gas infrared burner for better and even heat distribution
- Extra large infrared burner to cover large cooking area
- Instant heating up, no need to pre-heat
- Standby pilot for easy start
- Three rack positions Chrome coating wiring grid
- Zinc alloy knob with chrome coating
- Oil collector at the bottom
- Easy conversion from natural gas to Propane or vice versa
- Stainless steel in the front and sides
- Manual control
- 3/4" NPT rear gas connection

RCM Series - Salamanders

RCM-72



Temperature Range	BTUs (Natural Gas)	Dimensions - LxWxD mm / in
200°F - 400°F	60,000	580 / 22 3/4" 1829 / 72" 475 / 18 3/4"

- Gas salamander Gas infrared burner for better and even heat distribution
- Extra large infrared burner to cover large cooking area
- Instant heating up, no need to pre-heat
- Standby pilot for easy start
- Three rack positions Chrome coating wiring grid
- Zinc alloy knob with chrome coating
- Oil collector at the bottom
- Easy conversion from natural gas to Propane or vice versa
- Stainless steel in the front and sides
- Manual control
- 3/4" NPT rear gas connection